

Isolating valves

*Proflow
Ballofix®
has always
been a safe and
reliable solution.*

*Now it's constructed
with improved
materials to an
even better design.*



The original and genuine Ballofix®

NEW



Smoother ball rotation

NEW



Easy-to-operate handle

NEW



Handle colour options

Isolating valves

Suitable for a wide range of pipe systems

Proflow Ballofix® is available in more than 100 variants, suitable for a large range of applications in the plumbing and heating market. It's completely compatible with VSH Press, XPress press-fit and Tectite push-fit systems.



Proflow Ballofix® Press, with M press ends, suitable for copper pipe, using M jaws.



Proflow Ballofix® Press, with M press ends, suitable for steel pipe, using M jaws.



Proflow Ballofix® Push, with Tectite connections for copper pipe.*



Proflow Ballofix® Push, with Tectite connections for PEX when used with appropriate liner.*



Proflow Ballofix®, with threaded connections for steel pipe.



Proflow Ballofix®, with compression connections for copper and carbon steel up to 28mm.



Proflow Ballofix®, with compression connections suitable for PEX when used with appropriate liner.

*Proflow Ballofix®
technical helpline*
Tel 0870 120 0285

For sales information, please contact:

UK regions

Northern team

Tel 0870 120 0281 Fax 01302 560108
Email north.sales@pegler.yorkshire.co.uk

Southern team

Tel 0870 120 0282 Fax 01302 560458
Email south.sales@pegler.yorkshire.co.uk

Western team

Tel 0870 120 0283 Fax 01302 560109
Email west.sales@pegler.yorkshire.co.uk

Eastern team

Tel 0870 120 0282 Fax 01302 560458
Email east.sales@pegler.yorkshire.co.uk

Worldwide exports

Tel +44 (0) 1302 855656
Fax +44 (0) 1302 730513
Email export@pegler.yorkshire.co.uk

www.pegler.yorkshire.co.uk

Use new Proflow Ballofix® when you want to be sure.

